

www.oliviaceramic.in

OLIVIA

Feel Beautiful



APPLICATION AREAS :



Paths and
Walkways



Beach
Establishments



Swimming Pools
and Adjacent
Area



Public parks
And Gardens



Terraces



Street
Furnishing



Parking Areas,
Transitabl
Areas



Industrial
Areas

- 12 mm Thickness
- High Breaking Strength
- High M.O.R.
- 7 Colours Printing
- FLOTECH SURFACE

12 mm Thickness

FLOTECH SURFACE

www.oliviaceramic.in


OLIVIA

Feel Beautiful



Mountain
Rock

Heavy Duty
Parking Tiles




400x
400
MM

Just like Himalayan mountains act as barrier and protect the great indian plains and gives asthetic value to our mother land our floor tiles is reliable in all weather conditions and gives such a nice and asthetic look to your flooring area

Punch

400x400 MM Parking tiles


● Plain ★ Punch ▲ Rustic



2301



2302






2302

Punch

400x400 MM Parking tiles

● Plain ★ Punch ▲ Rustic



2303



2305





2303


Punch

400x400 MM Parking tiles


● Plain ★ Punch ▲ Rustic



2307



2308



2310



2311





2310 / 2311


Punch

400x400 MM Parking tiles

● Plain ★ Punch ▲ Rustic



2312



2313



2314



2316






2312
2313


Punch

400x400 MM Parking tiles


● Plain ★ Punch ▲ Rustic



2317



2318



2319



2320





2317
2318




2319
2320


Punch

400x400 MM Parking tiles


● Plain ★ Punch ▲ Rustic



2324



2325



2326





2324

Punch

400x400 MM Parking tiles

● Plain ★ Punch ▲ Rustic



2329



2330





Punch

400x400 MM Parking tiles


● Plain ★ Punch ▲ Rustic




2401



2402



2403



2404






2404

Punch

400x400 MM Parking tiles


● Plain ★ Punch ▲ Rustic




2407



2408



2410



2412





2407

Punch

400x400 MM Parking tiles


● Plain ★ Punch ▲ Rustic



2419



2417



2418







Punch

400x400 MM Parking tiles

● Plain ★ Punch ▲ Rustic



2413



2015





Punch

400x400 MM Parking tiles

● Plain ★ Punch ▲ Rustic



2602



2603



2606





2606

Punch

400x400 MM Parking tiles

● Plain ★ Punch ▲ Rustic



2609



2610






2610

Punch

400x400 MM Parking tiles


● Plain ★ Punch ▲ Rustic



2613



2614



2615



2616





Punch

400x400 MM Parking tiles

● Plain ★ Punch ▲ Rustic



2617







Punch

400x400 MM Parking tiles


● Plain ★ Punch ▲ Rustic



2701



2702



2707



2708




2701


Punch

400x400 MM Parking tiles


● Plain ★ Punch ▲ Rustic



2709



2710



2711





2709 / 2710

Punch

400x400 MM Parking tiles

● Plain ★ Punch ▲ Rustic



2901



2902



2903



2904





2904

Punch

400x400 MM Parking tiles

● Plain ★ Punch ▲ Rustic



2908



2909



2910



2915





2910

Glazed outdoor tiles -40x40cm (Group BIb)

TECHNICAL SPECIFICATIONS

CHARACTERISTICS	TEST METHOD	INTERNATIONAL STD	OUR VALUE
		ISO 13006/EN 176 (GROUP BIb)	
DIMENSION & SURFACE QUALITY			
Deviation in Length	ISO-10545-2	±0.6%	±0.2%
Deviation in Thickness	ISO-10545-2	±5%	±4 %
Straightness of Sides	ISO-10545-2	±0.5%	±0.2%
Rectangularity	ISO-10545-2	±0.6%	±0.2%
Surface Flatness	ISO-10545-2	±0.5%	±0.2%
PHYSICAL & THERMAL PROPERTIES			
Water Absorption	ISO-10545-3	0.5 to 3.0 %	0.5 to 1.0 %
Breaking Strength	ISO-10545-11	>1100 N	>1300 N
Flexural Strength (Modulus of Rupture)	ISO-10545-4	>30 N/mm2	>35 N/mm2
Mohs Hardness	EN-101	Depends on the product	Min. 4
Resistance to Surface Abrasion	ISO-10545-7	Depends on the product	PEI IV
Slip Resistance	ISO-10545-17	Depends on the product	R9
Frost Resistance	ISO-10545-12	Frost Proof	Frost Proof
Thermal Shock Resistance	ISO-10545-9	No Damage	No Damage
Moisture Expansion	ISO-10545-10	NIL	NIL
CHEMICAL PROPERTIES			
Resistance to low concentrations of acids and alkalis	ISO-10545-13	No Damage	GLA
Resistance to high concentrations of acids and alkalis	ISO-10545-13	No Damage	GHA
Resistance to household chemicals	ISO-10545-16	No Damage	Minimum GB
Resistance to Staining	ISO-10545-14	No Damage	Class 3

Packing Details

SIZE (in mm)	Thickness	No. of Tiles Per Box	Coverage Area	Weight Per Box (Approx)
400x400mm	12 mm (Approx)	5 / box	0.80 sq. mtr.	18.5 kg