

www.oliviaceramic.in

OLIVIA

Feel Beautiful



APPLICATION AREAS :



Paths and
Walkways



Beach
Establishments



Swimming Pools
and Adjacent
Area



Public parks
And Gardens



Terraces



Street
Furnishing



Parking Areas,
Transitable
Areas



Industrial
Areas

- 12 mm Thickness
- High Breaking Strength
- High M.O.R.
- 7 Colours Printing
- FLOTECH SURFACE

12 mm Thickness

FLOTECH SURFACE

www.oliviaceramic.in

OLIVIA

Feel Beautiful

Forest
Green



Heavy Duty
Parking Tiles



400x
400
MM

Just like Himalayan mountains act as barrier and protect the great indian plains and gives asthetic value to our mother land our floor tiles is reliable in all weather conditions and gives such a nice and asthetic look to your flooring area


Forest Green

400x400 MM Parking tiles

● Plain ★ Punch ▲ Rustic




1116



1117



1118



1124





1118

Forest Green

400x400 MM Parking tiles

● Plain ★ Punch ▲ Rustic



1203



1204



1211



1212





1204


Forest Green

400x400 MM Parking tiles


● Plain ★ Punch ▲ Rustic



1213



1302



1304



1308





1213



1302

Forest Green

400x400 MM Parking tiles


● Plain ★ Punch ▲ Rustic



1504



1507



1510






1504

Forest Green

400x400 MM Parking tiles


● Plain ★ Punch ▲ Rustic



1704



1707



1708



1711





1708

Forest Green

400x400 MM Parking tiles

● Plain ★ Punch ▲ Rustic



1713



1714



1715





1714

Forest Green

400x400 MM Parking tiles


● Plain ★ Punch ▲ Rustic



1907



2003



2006



2008





1907




2003


Forest Green

400x400 MM Parking tiles

● Plain ★ Punch ▲ Rustic



2010



2012



2309



2315





2309

Forest Green

400x400 MM Parking tiles

● Plain ★ Punch ▲ Rustic



2322



2414






2322

Forest Green

400x400 MM Parking tiles

● Plain ★ Punch ▲ Rustic




2405



2409



2411



2416





2405

Forest Green

400x400 MM Parking tiles


● Plain ★ Punch ▲ Rustic



2611



2605



2607







Forest Green

400x400 MM Parking tiles

● Plain ★ Punch ▲ Rustic



2704



2705



2706





2705

Forest Green

400x400 MM Parking tiles

● Plain ★ Punch ▲ Rustic



2905



2906





2906

Forest Green

400x400 MM Parking tiles

● Plain ★ Punch ▲ Rustic




2907



2912



2913



2914






2912


Forest Green

400x400 MM Parking tiles

● Plain ★ Punch ▲ Rustic



5001



5002



5003






5002


Forest Green

400x400 MM Parking tiles

● Plain ★ Punch ▲ Rustic



5076



5507



5513





5507


Forest Green

400x400 MM Parking tiles


● Plain ★ Punch ▲ Rustic




6001



6002



6004






6001


Forest Green

400x400 MM Parking tiles


● Plain ★ Punch ▲ Rustic



6005



6038



6042





6005

Glazed outdoor tiles -40x40cm (Group Blb)

TECHNICAL SPECIFICATIONS

CHARACTERISTICS	TEST METHOD	INTERNATIONAL STD	OUR VALUE
		ISO 13006/EN 176 (GROUP Blb)	
DIMENSION & SURFACE QUALITY			
Deviation in Length	ISO-10545-2	±0.6%	±0.2%
Deviation in Thickness	ISO-10545-2	±5%	±4 %
Straightness of Sides	ISO-10545-2	±0.5%	±0.2%
Rectangularity	ISO-10545-2	±0.6%	±0.2%
Surface Flatness	ISO-10545-2	±0.5%	±0.2%
PHYSICAL & THREMLAL PROPERTIES			
Water Absorption	ISO-10545-3	0.5 to 3.0 %	0.5 to 1.0 %
Breaking Strength	ISO-10545-11	>1100 N	>1300 N
Flexural Strength (Modulus of Rupture)	ISO-10545-4	>30 N/mm2	>35 N/mm2
Mohs Hardness	EN-101	Depends on the product	Min. 4
Resistance to Surface Abrasion	ISO-10545-7	Depends on the product	PEI IV
Slip Resistance	ISO-10545-17	Depends on the product	R9
Frost Resistance	ISO-10545-12	Frost Proof	Frost Proof
Thermal Shock Resistance	ISO-10545-9	No Damage	No Damage
Moisture Expansion	ISO-10545-10	NIL	NIL
CHEMICAL PROPERTIES			
Resistance to low concentrations of acids and alkalis	ISO-10545-13	No Damage	GLA
Resistance to high concentrations of acids and alkalis	ISO-10545-13	No Damage	GHA
Resistance to household chemicals	ISO-10545-16	No Damage	Minimum GB
Resistance to Staining	ISO-10545-14	No Damage	Class 3

Packing Details

SIZE (in mm)	Thickness	No. of Tiles Per Box	Coverage Area	Weight Per Box (Approx)
400x400mm	12 mm (Approx)	5 / box	0.80 sq. mtr.	18.5 kg